



EPM-U15S 系列概述

一. 电源规格:

电源型号 (MODEL)	输入 (VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
EPM-U15S3.3	100~240VAC	3.3V/4A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S5	100~240VAC	5V/3A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S6.5	100~240VAC	6.5V/2.5A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S9	100~240VAC	9V/1.7A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S12	100~240VAC	12V/1.3A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S15	100~240VAC	15V/1A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S24	100~240VAC	24V/0.65A	SCP/OCP/OVP	75mm*69mm*27mm
EPM-U15S48	100~240VAC	48V/0.3A	SCP/OCP/OVP	75mm*69mm*27mm

二. 系列特性:

Features:

- Universal AC input / Full range
- Compact size
- Protections: SCP /OCP
- Low cost, High reliability
- Cooling by free air convection
- 100% full load burn-in test
- 1 years warranty

三. 产品外观:




Net weight : 155g/pcs




四. 工作温度，输出功率曲线以及负载曲线图：

Temperature- load curve



Input voltage- load curve



五. 测试标准：

EMC DATA :

1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2


2、 EMS

ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz-80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms 60% 100ms >95% 5000ms	Criteria A
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	ENV50204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A

六. 安装尺寸:

build in dimension


unit: mm





七. 标签:

Spec Label




Connector define



八. 包装:

Packing

unit: mm



Inner Box

plane

solid

