



## ESM-H40S 系列概述

### 一. 电源规格:

电源型号 (MODEL)	输入(VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
ESM-H40S3.3	176VAC-240VAC	3.3V/8A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S5	176VAC-240VAC	5V/8A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S8	176VAC-240VAC	8V/5A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S12	176VAC-240VAC	12V/3.5A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S15	176VAC-240VAC	15V/2.7A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S24	176VAC-240VAC	24V/2A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S30	176VAC-240VAC	30V/1.5A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S36	176VAC-240VAC	36V/1.2A	SCP /OCP/OVP	143mm×59mm×38mm
ESM-H40S48	176VAC-240VAC	48V/1A	SCP /OCP/OVP	143mm×59mm×38mm

### 二. 系列特征:

#### Features

- AC input 176-240VAC only
- Compact size
- Protections: SCP /OCP/ OVP
- High efficiency
- Low cost, high reliability
- 100% full load burn-in test
- 1 years warranty


### 三. 产品外观:



net weight: 270g/pcs

四. 工作温度, 输出功率曲线:

### Temperature- load curve



五. 测试标准:

## EMC DATA:

### 1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2

### 2、 EMS

ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz-80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms 60% 100ms	Criteria A





		>95% 5000ms	
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	ENV50204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A

六. 安装尺寸:

build in dimension


unit: mm





### 七. 标签:

#### Spec Label




#### Connector define






八. 包装:

Packing unit: mm



Inner Box plane



solid

