



EPM-U15T 系列概述

一. 电源规格:

电源型号 (MODEL)	输入 (VAC)	输出 (VDC)	保护功能 (PROTECTION)	尺寸 (SIZE) MM
EPM-U15T5+9-9	100~240VAC	5V/1.5A; 9V/0.3A; -9V/0.3A	SCP/OCP	75mm*69mm*27mm
EPM-U15T5+12-5	100~240VAC	5V/2A; 12V/0.3A; -5V/0.3A	SCP/OCP	75mm*69mm*27mm
EPM-U15T5+12-12	100~240VAC	5V/1.5A; 12V/0.3A; -12V/0.3A	SCP/OCP	75mm*69mm*27mm
EPM-U15T5+15-15	100~240VAC	5V/1.5A; 15V/0.3A; -15V/0.3A	SCP/OCP	75mm*69mm*27mm
EPM-U15T5+18-18	100~240VAC	5V/1.5A; 18V/0.3A; -18V/0.3A	SCP/OCP	75mm*69mm*27mm

二. 系列特性:

Features:

- Universal AC input / Full range
- Compact size
- Protections: SCP /OCP
- Low cost, High reliability, High efficiency
- Cooling by free air convection
- 100% full load burn-in test
- 1 years warranty

三. 产品外观:




Net weight : 155g/pcs




四. 工作温度, 输出功率曲线以及负载曲线图:

Temperature- load curve



Input voltage- load curve



五. 测试标准:

EMC DATA:

1、 EMI

RE/CE	EN55022 CLASS A
Harmonics Current	EN61000-3-2

2、 EMS


ESD	EN61000-4-2	Air:8KV Contact:4KV	Criteria A
RS	EN61000-4-3	80MHz~1GHz 3V/m	Criteria A
EFT	EN61000-4-4	5KHz AC=1KV	Criteria A
Surge Test	EN61000-4-5	1.2/50us AC:±2KV 8/50us	Criteria A
CS	EN61000-4-6	0.15MHz-80MHz 3V/m	Criteria A
Voltage dips	EN61000-4-8	30% 10ms 60% 100ms >95% 5000ms	Criteria A
Power Frequency Magnetic Field	EN61000-4-11	50Hz 30A/m	Criteria A
RF Electromagnetic Field pulse modulated	ENV50204	900±5MHz 200Hz 3V/m, 50%Duty cycle	Criteria A



六. 安装尺寸:

build in dimension


unit: mm






七. 标签:

Spec Label




Connector define




八. 包装:

Packing unit: mm



Inner Box plane



solid

